

BEST AVAILABLE COPY

PATENT SPECIFICATION

DRAWINGS ATTACHED

Inventor: WILLIAM ROBERT STEPHENSON

886.743



Date of filing Complete Specification Nov. 27, 1959.

Application Date Dec. 8, 1958.

No. 39512/58.

Complete Specification Published Jan. 10, 1962.

GT. BRIT.
DIV.

Index at acceptance:—Classes 103(2), C4; and 78(4), E18.

International Classification:—B02d. B62d.

COMPLETE SPECIFICATION

Apparatus for Attachment to Roof Racks of Road Vehicles

We, S. E. D. (CIRENCESTER) LIMITED, a British Company, of Love Lane, Cirencester, Gloucestershire, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to apparatus to be detachably fitted to roof racks of road vehicles which enables large unwieldy articles, for example boats, to be transferred to and from the roof of a vehicle with ease and safety.

According to the invention such apparatus comprises a freely rotatable transfer roller, a freely rotatable guide roller extending substantially at right angles to said transfer roller and means for detachably securing said rollers to the roof rack of a vehicle with the transfer roller extending transversely and the guide roller extending upwardly in relation to the vehicle.

One embodiment of the invention is shown in the accompanying drawings, wherein:—

Figure 1 is a perspective view of the apparatus mounted on the roof rack of a motor car, and

Figure 2 is a fragmentary perspective view, on an enlarged scale and partly in section, of one of the sets of rollers of Figure 1 and its clamping means.

As shown, the apparatus is in two identical parts, each of which includes a transfer roller 1 rotatably mounted on a tubular metal member 2 (Fig. 2) extending beyond the ends of the roller for engagement by the upper sets of jaws of a pair of clamping members 3 which also serve to limit axial movement of the roller. Secured to one end of the member 2, for example by welding, is a shorter tubular member 4 extending at right angles to the member 2 and carrying a freely rotatable guide roller 5 axially confined thereon by a split pin 6 or the like.

[Price 4s. 6d.]

By engaging the lower sets of jaws of the outer clamping members around a transverse member 7 of the roof rack through the intermediary of a split cylinder 8 and those of the inner clamping members around a connecting member 9 of the roof rack the two parts of the apparatus may be secured in position on the rack with the transfer rollers arranged coaxially to form in effect a single transverse roller provided at its ends with upstanding guide rollers. The gap between the inner ends of the two transfer rollers 1 is not sufficient to affect the efficient operation of the apparatus while enabling the combined axial length of the transfer rollers to be adjusted to the width of the article to be accommodated.

The apparatus of the invention is particularly advantageous when it is desired to transport a small boat by car. With the apparatus in position on the roof rack one end of the boat is lifted into contact with the transfer rollers 1 and the boat can then be pushed easily into position on the roof of the car by one person.

In a modification (not shown) the outer of each pair of clamping members has its upper set of jaws at a greater height than the corresponding jaws on the inner clamping members. The consequent upward inclination of the transfer rollers from the centre outwards provides central clearance for the accommodation of projecting portions, such as the centre parts of convex decks of boats, without their being scratched by the inner ends of the rollers and their clamping means.

To prevent scratching of paintwork or other surfaces of a boat or other article it is preferred to employ rollers of synthetic plastic or other non-abrasive material which will operate as pads.

The apparatus is preferably attached to the rear end only a roof rack but an additional

device may also be attached to the front end.

WHAT WE CLAIM IS:—

1. Apparatus for facilitating the transfer of objects to and from the roof of a vehicle, comprising a freely rotatable transfer roller, a freely rotatable guide roller extending substantially at right angles to said transfer roller and means for detachably securing said rollers to the roof rack of a vehicle with the transfer roller extending transversely and the guide roller extending upwardly in relation to the vehicle.

2. Apparatus according to Claim 1, wherein the transfer roller is rotatably mounted upon a tubular member the ends of which extend beyond the ends of the transfer roller for engagement by said securing means.

3. Apparatus according to Claim 2, wherein said securing means consist of clamping members each of which has two sets of jaws one for engaging an end of said tubular member and the other for engaging a transverse member of a vehicle roof rack.

4. Apparatus according to Claim 2 or 3, wherein said guide roller is rotatably mounted on a second tubular member, one end of which extends beyond one end of said guide roller and is secured to one end of said first tubular member.

5. Apparatus according to Claim 4, wherein the other end of said second tubular member extends beyond the other end of said guide roller and is provided with means for limiting axial movement of said roller.

6. Apparatus according to Claim 5, wherein said limiting means is a split pin passing transversely through said second tubular member.

7. Apparatus according to any one of Claims 2 to 6, wherein said tubular members are made of metal.

8. Apparatus according to any preceding claim, wherein said rollers are made of synthetic or other non-abrasive material.

9. A vehicle roof rack provided with apparatus as claimed in any preceding claim.

10. A vehicle roof rack according to Claim 9, wherein two transfer rollers are arranged co-axially with guide rollers situated at the ends thereof remote from one another, and said securing means permits axial adjustment of said rollers towards and away from one another to vary the width of the apparatus to suit the size of the object to be carried.

11. A vehicle roof rack according to Claim 10, wherein the remote ends of said transfer rollers are raised relatively to the adjacent ends thereof.

12. A vehicle roof rack according to any one of Claims 9 to 11, wherein said apparatus is fitted to the rear end thereof.

13. Apparatus for facilitating the transfer of objects to and from the roof of a vehicle, substantially as hereinbefore described and as shown in Fig. 2 of the accompanying drawings.

14. A vehicle roof rack provided with apparatus for facilitating the transfer of objects thereto and therefrom, substantially as hereinbefore described and as shown in the accompanying drawings.

HERON ROGERS & CO.,

Agents for Applicants,

Bridge House, 181, Queen Victoria Street,
London, E.C.4.

PROVISIONAL SPECIFICATION

Apparatus for Attachment to Roof Racks of Road Vehicles

We, S. E. D. (CIRENCESTER) LIMITED, a British Company, of Love Lane, Cirencester, Gloucestershire, do hereby declare this invention to be described in the following statement:—

This invention relates to roof racks for road vehicles and to a device to be detachably fitted thereon which enables large unwieldy articles, for example boats, to be transferred to and from the roof of a vehicle with ease and safety.

According to the invention such a device includes one or more freely rotatable transfer rollers, freely rotatable guide rollers extending substantially at right angles to the transfer roller or rollers and means for detachably securing the device to the roof rack of a car or other road vehicle.

In a preferred construction the device is in two identical parts each of which includes a transfer roller rotatably mounted on a tubular metal member extending beyond the ends of

the roller for engagement by the upper sets of jaws of a pair of clamping members which also serve to limit axial movement of the roller. Secured to one end of the tubular member, for example, by welding, is a shorter tubular member extending at right angles to the first member and carrying a freely rotatable guide roller axially confined thereon by a split pin or the like.

By engaging the lower sets of jaws of the clamping members around a transverse member of the roof rack the two parts of the device may be secured in position on the rack with the transfer rollers arranged co-axially to form in effect a single transverse roller provided at its ends with upstanding guide rollers. The gap between the inner ends of the two transfer rollers is not sufficient to effect the efficient operation of the device while enabling the combined axial length of the transfer rollers to be adjusted to the width of the article to be accommodated.

The device of the advantageous when i small boat by car. W on the roof rack one into contact with th boat can then be p on the roof of the c To prevent scratch surface damage to a preferred to employ

lpton Spa: Printed fo led at The Patent Off

BEST AVAILABLE COPY

886,743

3

according to any one of
wherein said tubular members

according to any preceding
rollers are made of syn-
-abrasive material.

rack provided with appar-
any preceding claim.

of rack according to Claim
transfer rollers are arranged
dc rollers situated at the
e from one another, and
permits axial adjustment
wards and away from one
width of the apparatus to
object to be carried.

rack according to Claim
note ends of said transfer
relatively to the adjacent

f rack according to any
l, wherein said apparatus
nd thereof.

facilitating the transfer
m the roof of a vehicle,
before described and as
the accompanying draw-

of rack provided with
ing the transfer of ob-
refrom, substantially as
l and as shown in the
s.

HERON ROGERS & CO.,
Applicants,
Queen Victoria Street,
E.C.4.

d Vehicles

it by the upper sets of
ipping members which
ial movement of the
end of the tubular
welding, is a shorter
ng at right angles to
arrying a freely rotat-
confined thereon by

r sets of jaws of the
nd a transverse mem-
ie two parts of the
position on the rack
arranged co-axially
gle transverse roller
th upstanding guide
the inner ends of the
it sufficient to effect
f the device while
axial length of the
isted to the width of
dated.

The device of the invention is particularly
advantageous when it is desired to transport a
small boat by car. With the device in position
on the roof rack one end of the boat is lifted
into contact with the transfer rollers and the
boat can then be pushed easily into position
on the roof of the car by one person.

To prevent scratching of paintwork or other
surface damage to a boat or other article it is
preferred to employ rollers of synthetic plastic

or other non-abrasive material which will
operate as pads.

The device is preferably attached to the
rear end only of a roof rack but an additional
device may also be attached to the front end.

HERON ROGERS & CO.,

Agents for Applicants,

Bridge House, 181, Queen Victoria Street,
London, E.C.4.

London Spa: Printed for Her Majesty's Stationery Office, by the Courier Press.—1962.

and at The Patent Office, 25, Southampton Buildings, London, W.C.2, from which copies may be obtained.

224-42-1F
310

14

3.10.1962 JJ

886,743

COMPLETE SPECIFICATION

1 SHEET

This drawing is a reproduction of the Original on a reduced scale.

BEST AVAILABLE COPY

FIG.2




FIG.1

